## **NEW PRODUCT INFORMATION**

Simplified transfer of measurement data

## **USB Input Tool Direct**



- > USB system for direct connection as a keypad format without software driver (HID) or as a virtual COM port (VCP) with fixed COM port assignment in Windows
- > USB ITPAK software for transferring measurement values in text format (when used as a VCP)
- > USB ITPAK software for simplified creation of log journals in Excel
- > Windows 2000/XP/Vista/Windows 7 compatible



Application	Situation	USB-ITPAK software	Data format
Use of any software that requires keypad input	1. Only one USB Input Tool signal line is required	Software is not required	Measurement value in keypad format (HID=Human Interface Device)
Commonly available statistics software, e.g., Mitutoyo MeasurLink	2. Requires one USB Input Tool signal line and USB-ITPAK software	Assigns a fixed virtual COM port (VCP) for each measuring device (cable). Then becomes inactive.	MUX-10 specification (e.g., 01A+138.626) with fixed COM assignment for channel identification
Any software application that requires keypad input, e.g., Word, .txt format		<ul> <li>Connected measuring devices and foot switches are selected and assigned</li> <li>Determines the suffix</li> <li>Stores a sequence as part program</li> </ul>	Measurement values are transferred in text format (VCP = Virtual COM Port)
Excel		<ul> <li>Connected measuring devices and foot switches are selected and assigned</li> <li>Completely organizes the Excel spreadsheet, i.e., transferred measurement values are entered in pre-defined target cells</li> </ul>	Measurement record in Excel format and string with max. 31 characters (e.g., text input)

## Benefits of the new Digimatic USB connections

## USB plug-in connection to the measuring device

Nr.	Model	Designation
06ADV380A	А	High-grade IP protected model with data key
06ADV380B	В	High-grade IP protected model with data key
06ADV380C	С	With data key
06ADV380D	D	10 pin, simple model
06ADV380E	E	6 pin, round model
06ADV380F	F	Simple, straight model
06ADV380G	G	High-grade IP protected dial indicator



Note: All information about our products in this printed material, particularly the illustrations, drawings, measurement and performance specifications, as well as other technical specifications are to be interpreted as approximate average values. In this respect, changes in construction, technical specification, measures and weights remain reserved. Our specified standards, similar technical regulations as well as the technical specifications, descriptions and illustrations of products are accurate on the date of printing. Furthermore, our general terms of business in the currently applicable revision are binding. Only the offers we make are definitive.



Vision Measuring Systems	
3,	
Form Measurement	
Optical Measuring	
5	
Sensor Systems	
Test Equipment and	
Seismometers	
Jeismonieters	
Digital Scale and DRO Systems	
Digital Scale and Dive Systems	
Concell To all Justimum and a soul	
Small Tool Instruments and	
Data Management	

Mitutoyo Europe GmbH Borsigstr. 8-10 41469 Neuss T +49 (0) 21 37-102-0 F +49 (0) 21 37-102-351 info@mitutoyo.eu www.mitutoyo.eu

