



### ENVIROMENTAL QUALITY METER WITH SOUND 850069

6 meters in one

Air Speed

Air Temperature

Humidity

Light

Sound

Thermocouple Temperature

|                 | Range                      | Resolution | Accuracy                                       |
|-----------------|----------------------------|------------|--|
| °C Ambient      | 0 ~ 50                     | 0.1        | ±1.2°C   |
| °F Ambient      | 32 ~ 122                   | 0.1        | ±2.5°F   |
| °C Type K       | -100 ~ 1300                | 0.1        | ±(1% + 1°C)                                    |
| °F Type K       | -148 ~ 2372                | 0.1        | ±(1% + 2°F)                                    |
| RH              | 10 ~ 95%                   | 0.1        | < 70% RH ± 4%<br>> 70% RH ± (4% rdg + 1.2% RH) |
| Airspeed m/s    | 0.4 ~ 30.0                 | 0.1        | 20 m/s ±3% fs                                  |
| Airspeed km/h   | 1.4 ~ 108.0                | 0.1        |  |
| Airspeed mile/h | 0.9 ~ 67.0                 | 0.1        |  |
| Airspeed knots  | 0.8 ~ 58.3                 | 0.1        |  |
| Airspeed ft/min | 80 ~ 5910                  | 1          |  |
| Lux             | 0 ~ 2,000<br>1800 ~ 20,000 | 1<br>10    | ±5% rdg + 8d                                   |
| Foot Candle     | 0 ~ 204.0<br>170 ~ 1860    | 0.1<br>1   |  |
| dB              | 35 ~ 130                   | 0.1        | 23 + 5°C ± 1.5dB                               |

Combines an anemometer, hygrometer, thermometer, sound and light meter into a single hand-held unit. Also reads any type-K thermocouple probe. Results are displayed on a large dual LCD with low battery and out-of-range indications. Features touch-tone buttons, min/max, auto power off and hold functions. Comes ready to use in a soft carrying case with RS232 computer port, instructions, 6 AAA batteries, easel back, and a tripod screw. N.I.S.T. traceable certificate of calibration available.

**Dimensions:** 9¾" × 2¾" × 1¼" (248 × 70 × 32 mm)

**Weight:** 12 oz (340 g)

### OPTIONAL ACCESSORIES

800060-77 Type-K Thermocouple Probes

840057 RS232 Cable

840058 USB Power Cable

840094 RS232 to USB Adaptor Cable

840097 AC Adaptor

850016 2 Pt. Acoustical Calibrator

850080 Intelligent Software

840091 Sound Meter Windscreen

840093 Field Tripod



A2B-Lab

Rue Ibnou Katir - Résidence El Beida,

Imm. B, Apt. 22 20380 Casablanca - Maroc

Tél: +212 (0)5 22 98 66 19

Email: contact@a2b-lab.ma

Web: www.a2b-lab.ma